

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

COMPANY NAME:	AMERICAN INDUSTRIES, INC.	PRODUCT NAME:	P1
ADDRESS LINE 1:	4300 Kahn Drive, Box 1405	PRODUCT CODE:	1681
ADDRESS LINE 2:	Lumberton, NC 28359-1405 USA	PRODUCT USE:	Food Grade Foaming Lubricant
TELEPHONE NUMBERS:	800-753-5153 (or) 910-738-7224	SDS FILE ID:	1681.02
EMERGENCY PHONE:	CHEMTREC 1-800-424-9300	SDS DATE:	2015-04-17
		REPLACES VERSION DATED:	2012-12-03 and all prior versions

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification

Aerosol

Category 1

Label elements



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurized container may burst if heated.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P412 Do not expose to temperatures exceeding 122°F (50°C).
P403 Store in a well ventilated place

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u>	<u>CAS number</u>	<u>%</u>
Mineral Oil, Slab Oil	0008042-47-5	51-90
Propane	0000074-98-6	5-11
Soybean oil, Me ester	0067784-80-9	5-10
Butane	0000106-97-8	2-4

SECTION 4: FIRST AID MEASURES

Inhalation	Remove source of exposure or move person to fresh air and keep comfortable for breathing. If exposed/feel unwell/concerned: Call a POISON CENTER/doctor/ Eliminate all ignition sources if safe to do so.
Skin contact	Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Gently blot or brush away excess product. Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. Call a POISON CENTER/doctor if you feel unwell. Store contaminated clothing under water and wash before reuse or discard.
Eye contact	Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Ingestion Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor/. If vomiting occurs naturally, lie on your side, in the recovery position. Never give anything by mouth to an unconscious or convulsing victim. Keep person warm and quiet.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable extinguishing media Use water, fog, dry chemical, or carbon dioxide. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Unsuitable extinguishing media Water may be ineffective but can be used to cool containers exposed to heat or flame

Specific hazards arising from the chemical Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Aerosol cans may rupture when heated. Heated cans may burst. In fire, will decompose to carbon dioxide, carbon monoxide.

Special protective equipment and precautions for firefighters Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear. Care should always be exercised in dust/mist areas.

Fire-fighting procedures Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Flammable/combustible material. ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stay upwind; keep out of low areas. Immediately turn off or isolate any source of ignition. Keep unnecessary people away; isolate hazard area and deny entry. Do not touch or walk through spilled material. Clean up immediately. Use absorbent sweeping compound to soak up material and put into suitable container for proper disposal.

Methods and materials for containment and cleaning up ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area). Use explosion proof equipment. Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental precautions Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Recommended Equipment Positive pressure, full-face piece self-contained breathing apparatus(SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling For industrial and institutional use only. For use by trained personnel only. Keep away from children. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous. Do not cut, drill, grind, weld, or perform similar operations on or near containers. Do not pressurize containers to empty them. Ground all structures, transfer containers and equipment to conform to the national electrical code. Use procedures that prevent static electrical sparks. Static electricity may accumulate and create a fire hazard. Store at temperatures below 120°F (49°C)..

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Component</u>	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA Tables Z1,2,3	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	<u>ACGIH</u> <u>TWA</u> (ppm)
Butane				800	1900	1000
Propane	1000	1800	1	1000	1800	See Appendix F: Minimal Oxygen Content
Eye/face protection	Chemical goggles, safety glasses with side shields or vented/splash proof goggles. Contact lenses may absorb irritants. Particles may adhere to lenses and cause corneal damage					
Skin protection	Wear gloves, long sleeved shirt, long pants and other protective clothing as required to minimize skin contact. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Chemical-resistant clothing is recommended to avoid prolonged contact. Avoid unnecessary skin contact.					
Respiratory protection	If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapors. When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.					

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Color	Clear Amber
Form	Aerosol
Flash point	Below 73°F (23°C)
Density	6.51770 lb/gal
Density VOC	0.84730 lb/gal
% VOC	13%
VOC Actual	0.84730 lb/gal
VOC Actual	101.53214 g/l
VOC Regulatory	0.84730 lb/gal
VOC Regulatory	101.53214 g/l
Melting point/boiling point	N/A
Auto-igniting	N/A
pH	N/A
Solubility in water	N/A
Vapor density	Slower than ether
Vapor pressure	N/A
Viscosity	N/A

Evaporation Rate	Slower than ether
VOC Composite Partial Pressure	5371.68 mmhg (Calculated @ 68°F (20°C))

SECTION 10: STABILITY AND REACTIVITY

Chemical stability	Stable
Possibility of hazardous reactions	Will not occur.
Conditions to avoid	High temperatures.
Hazardous decomposition products	In fire, will decompose to carbon monoxide and carbon dioxide.
Incompatible materials	None known.

SECTION 11: TOXICOLOGICAL INFORMATION

Skin contact	Overexposure will cause defatting of skin.
Eye contact	Eye irritant. Overexposure will cause redness and burning sensation.
Symptoms related to the physical, chemical and toxicological characteristics	No sensitizing data available.
Specific target organ toxicity	No data available.
Acute Effects	Inhalation: effect of overexposure include irritation of respiratory tract, headache, dizziness, nausea, and loss of coordination. Extreme overexposure may result in unconsciousness and possibly death. Butane (0000106-97-8) LC50 (mouse): 202000 ppm (481000 mg/m3) (4-hour exposure); cited as 680 mg/L (2-hour exposure) (9) LC50 (rat): 276000 ppm (658000 mg/m3) (4-hour exposure); cited as 658 mg/L (4-hour exposure) (9)
Germ Cell Mutagenicity	No data available.
Carcinogenicity	No data available.
Reproductive Toxicity	No data available.
Respiratory or Skin Sensitization	No data available.
Specific Target Organ Toxicity-Single & Repeated Exposure	No data available.
Aspiration Hazard	Aspiration hazard if swallowed.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity	No data available.
Persistence and degradability	No data available.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal instructions	Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws. Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.
-----------------------	--

SECTION 14: TRANSPORT INFORMATION

DOT Consumer Commodity, ORM-D

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

SECTION 15: REGULATORY INFORMATION

COMPONENT	(CAS/PERC)	REGULATION
Propane	(0000074-98-6) 5-11%	SARA 312, VOC, TSCA, ACGIH, OSHA
Butane	(0000106-97-8) 2-4%	SARA 312, VOC, TSCA, ACGIH
Mineral Oil, Slab Oil	(0008042-47-5) 51-90%	SARA 312, TSCA
Soybean oil, Me ester	(0067784-80-9) 5-10%	SARA 312, TSCA

* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS.

SECTION 16: OTHER INFORMATION

Hazardous Materials Identification System (HMIS)

HMIS-RATING:	
HEALTH	0
FLAMMABILITY	3
PHYSICAL HAZARD	0

Important Note: *To be the best of our knowledge, the information contained herein is accurate. However there is no assumption of liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer/supplier, the manufacturer/supplier will not be responsible for loss, injury, or expense arising out of the products improper use. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.*

End of SDS