SAFETY DATA SHEET



SECTION 1: IDENTIFICATION

COMPANY NAME:	AMERICAN INDUSTRIES, INC.	PRODUCT NAME:	MAXIMUS
ADDRESS LINE 1:	4300 Kahn Drive, Box 1405	PRODUCT CODE:	2347
ADDRESS LINE 2:	Lumberton, NC 28359-1405 USA	PRODUCT USE:	Low Foam Floor scrubber concentrate
TELEPHONE NUMBERS:	800-753-5153 (or) 910-738-7224	SDS FILE ID:	2347.06
EMERGENCY PHONE:	CHEMTREC 1-800-424-9300	SDS DATE:	2023-09-20
		REPLACES MSDS VERSIC	N DATED: 2016-02-23 and all prior revisions

SECTION 2: HAZARDS IDENTIFICATION

SECTION 2. HAZARDS IDENT	IFICATION			
GHS Classification:				
Health	Skin corrosion/ir	ritation		1
	-	age/eye irritation		1
	Carcinogenicity			2
Environmental hazards	Not classified.			
OSHA defined hazards	Not classified.			
Label elements	$\wedge \wedge$			
	\checkmark \checkmark			
Signal word	DANGER			
Hazard statements:	Causes severe sk	in burns and eye c	lamage. Causes serious e	ye damage. Suspected of causing cancer.
Precautionary statements:				
Prevention	understood. Do	not breathe mist/v	apors. Wash thoroughly	III safety precautions have been read and after handling. Wear protective
Response	• •		tection/face protection.	N SKIN (OR HAIR): Remove all
Response			_	shower. IF INHALED: Remove
		-	-	N EYES: Rinse cautiously with
		-	_	t and easy to do. Continue
	rinsing. Immedia	tely call a poison c	enter/doctor. Wash cont	aminated clothing before reuse.
Storage	Store locked up.			
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.			
Hazard(s) not otherwise	None known.			
classified (HNOC)	None known.			
Supplemental information	8.65% of the mix	ture consists of co	mponent(s) of unknown	acute oral toxicity. 11.45% of
				mal toxicity. 95.97% of the
			of unknown acute inhalat	ion toxicity.
SECTION 3: COMPOSITION/I	NFORMATION ON		0/	
<u>Chemical name</u> Diphosphoric acid, potassium	salt (1·/)	<u>CAS number</u> 7320-34-5	<u>%</u> 3.002	
Silicic acid (H2SiO3), disodium	n salt (1:2)	6834-92-0	2.802	
Ethanol, 2,2',2"-Nitrilotris-		102-71-6	1.276	
Ethanol, 2,2'-Iminobis-		111-42-2	0.225	
Benzaldehyde, 4-Hydroxy-3-N	/lethoxy-	121-33-5	0.012	
Sodium Hydroxide (NA(OH))		1310-73-2	0.012	
Benzaldehyde		100-52-7	0.003	
Other components below reportable levels			92.666	

SECTION 4: FIRST AID MEASURES

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Immediately remove all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed Indication of immediate	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water
medical attention and special treatment needed	immediately. While flushing, remove clothes which do not adhere to affected area. Cal an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms my be delayed.
General information	If exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of material(s) involved, and take precautions to protect themselves.
SECTION 5: FIRE-FIGHTING M	IEASURES
Extinguishing media	Water fog, foam, dry chemical powder, carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
equipment, motifications	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
	Use standard firefighting procedures and consider the hazards of other involved materials. No unusual fire or explosion hazards noted.
Specific methods	No unusual fire or explosion hazards noted.
Specific methods General fire hazards	No unusual fire or explosion hazards noted. EASE MEASURES Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal
Specific methods General fire hazards SECTION 6: ACCIDENTAL RELL Personal precautions, protective equipment and	No unusual fire or explosion hazards noted. EASE MEASURES Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate
Specific methods General fire hazards SECTION 6: ACCIDENTAL RELL Personal precautions, protective equipment and emergency procedures Methods and materials for	No unusual fire or explosion hazards noted. EASE MEASURES Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Prevent entry into waterways, sewer, basements, or confined areas. Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand, or earth and place into containers. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (e.g. clothe, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled
Specific methods General fire hazards SECTION 6: ACCIDENTAL RELL Personal precautions, protective equipment and emergency procedures Methods and materials for	No unusual fire or explosion hazards noted. EASE MEASURES Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Prevent entry into waterways, sewer, basements, or confined areas. Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand, or earth and place into containers. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (e.g. clothe, fleece). Clean surface thoroughly to remove residual contamination.
Specific methods General fire hazards SECTION 6: ACCIDENTAL RELU Personal precautions, protective equipment and emergency procedures Methods and materials for containment and cleanup	No unusual fire or explosion hazards noted. EASE MEASURES Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Prevent entry into waterways, sewer, basements, or confined areas. Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand, or earth and place into containers. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (e.g. clothe, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses, or onto the ground.
Specific methods General fire hazards SECTION 6: ACCIDENTAL RELL Personal precautions, protective equipment and emergency procedures Methods and materials for containment and cleanup	No unusual fire or explosion hazards noted. EASE MEASURES Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Prevent entry into waterways, sewer, basements, or confined areas. Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand, or earth and place into containers. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (e.g. clothe, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses, or onto the ground. STORAGE Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Specific methods General fire hazards SECTION 6: ACCIDENTAL RELL Personal precautions, protective equipment and emergency procedures Methods and materials for containment and cleanup Environmental precautions SECTION 7: HANDLING AND S	No unusual fire or explosion hazards noted. EASE MEASURES Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Prevent entry into waterways, sewer, basements, or confined areas. Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand, or earth and place into containers. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (e.g. clothe, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses, or onto the ground. STORAGE Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Store locked up. Store in tightly closed container. Store away from incompatible materials (see section
Specific methods General fire hazards SECTION 6: ACCIDENTAL RELU Personal precautions, protective equipment and emergency procedures Methods and materials for containment and cleanup Environmental precautions SECTION 7: HANDLING AND S Handling Storage	No unusual fire or explosion hazards noted. EASE MEASURES Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Prevent entry into waterways, sewer, basements, or confined areas. Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand, or earth and place into containers. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (e.g. clothe, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses, or onto the ground. STORAGE Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Personal protective equipment	established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product. The following are recommendations for Personnel Protective Equipment (PPE). The employers/user of this product must perform a Hazard Assessment of the workplace according to OSHA regulations 29 CFR 1910.132 to determine the appropriate PPE for use while performing any task involving potential exposure to this product
Eye/Face protection	Chemical respirator with organic vapor cartridge and full facepiece.
Skin protection	Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	Chemical respirator with organic vapor cartridge and full facepiece.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the materials and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Occupational exposure limits

	US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)						
	Components	CAS #		Value		Туре	Form
	Sodium Hydroxide (NA(OH)) US ACGIH Threshold	1310-73-2 Limit Values		2 mg/m3		PEL	
	Ethanol, 2,2',2"-	102-71-6		5 mg/3		TWA	
	Nitrilotris-			-			
	Ethanol, 2,2'-Iminobi	s- 111-42-2		1 mg/m3		TWA	Inhalable fraction and
	Sodium Hydroxide (NA(OH))	1310-73-2		2 mg/m3		CEILING	vapor
	US NIOSH Pocket Gui	ide to Chemical Hazai	rds				
	Ethanol, 2,2'-Iminobi	s- 111-42-2		15 mg/m3		TWA	
	Sodium Hydroxide (NA(OH))	1310-73-2		2 mg/m3		CEILING	
	US Workplace Enviro	nmental Exposure Le	vel (WEEL) Gu	iides			
	Benzaldehyde	100-52-7		17.4 mg/m3 4 PPM		STEL	
				8.7 mg/m3 2 ppm		TWA	
	Benzaldehyde, 4- Hydroxy-3-Methoxy-	121-33-5		10 mg/m3		TWA	
Biologic	cal limit values		xposure limits	noted for the ingr	edient(s)		
Exposu	re guidelines						
	US – California OELs:	Skin designation					
	Ethanol, 2,2'-Iminobi	s- 111-42-2		Can be absorbed	d through	the skin.	
	US ACGIH Threshold	Limit Values: Skin des	signation				
	Ethanol, 2,2'-Iminobi	s- 111-42-2		Can be absorbed	d through	the skin.	
SECTIO	N 9: PHYSICAL AND CI		S				
Color		Green liquid					
Physica	l State	Liquid					
Odor Th	arachald	Strawberry Not available.					
	nreshold	Not available.					
Flash po							
	n Coefficient	Not available. 219.88°F (104.38°C)	octimated				
Boiling	μοπι	219.00 F (104.38 C	estinateu				

SDS File ID: 2347.06

Melting point/freezing point	Not available.	
Auto-ignition temperature	Not available.	
Vapor pressure	Not available.	
Vapor density	Not available.	
Specific gravity	1.05	
Viscosity	Not available.	
Water solubility	Not available.	
рН	12	
Evaporation rate (Water=1)	Not available.	
Flammability (solid, gas)	Not applicable.	
Decomp Temp	Not available.	
Density	8.77 lbs/gal, 1.05 gml	
Explosive properties	Not explosive.	
Oxidizing properties	Not oxidizing.	
Percent volatile	85% estimated	
VOC	0.11% estimated	
SECTION 10: STABILITY AND I	REACTIVITY	
Reactivity	The product is stable and non-reactive	e under normal conditions of use, storage, and transport
Chemical stability	Stable under normal conditions.	
Possibility of hazardous reactions	Hazardous polymerization does not o	ccur.
Conditions to avoid	Contact with incompatible materials.	
Incompatible materials	Strong oxidizing agents.	
Hazardous decomposition	No hazardous decomposition product	s are known.
-		
products		
products SECTION 11: TOXICOLOGICAL		
products SECTION 11: TOXICOLOGICAL Information on likely routes of	fexposure	ratory system. Prolonged inhalation may be harmful
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation	f exposure May cause irritation to the respir	ratory system. Prolonged inhalation may be harmful.
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact	f exposure May cause irritation to the respir Causes severe skin burns.	ratory system. Prolonged inhalation may be harmful.
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact	f exposure May cause irritation to the respin Causes severe skin burns. Causes serious eye damage.	ratory system. Prolonged inhalation may be harmful.
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion	f exposure May cause irritation to the respin Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns.	
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the	f exposure May cause irritation to the respin Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv	e skin damage. Causes serious eye damage. Symptoms may
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion	f exposure May cause irritation to the respin Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv	
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and	f exposure May cause irritation to the respir Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result.	e skin damage. Causes serious eye damage. Symptoms may
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics	f exposure May cause irritation to the respir Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result.	e skin damage. Causes serious eye damage. Symptoms may
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics Information on toxicological	f exposure May cause irritation to the respin Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result. effects	e skin damage. Causes serious eye damage. Symptoms may
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics Information on toxicological Acute toxicity	f exposure May cause irritation to the respir Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result. effects Not known.	e skin damage. Causes serious eye damage. Symptoms may
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics Information on toxicological Acute toxicity Benzaldehyde	f exposure May cause irritation to the respin Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result. effects Not known. 100-52-7	e skin damage. Causes serious eye damage. Symptoms may 5, swelling, and blurred vision. Permanent eye damage including
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics Information on toxicological Acute toxicity Benzaldehyde	f exposure May cause irritation to the respir Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result. effects Not known. 100-52-7 LD50 Dermal-rabbit	e skin damage. Causes serious eye damage. Symptoms may s, swelling, and blurred vision. Permanent eye damage including >1,250 mg/kg
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics Information on toxicological Acute toxicity Benzaldehyde Acute toxicity Benzaldehyde, 4-Hydroxy-3- Methoxy	f exposure May cause irritation to the respir Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result. effects Not known. 100-52-7 LD50 Dermal-rabbit LD50 Oral-rat 121-33-5	e skin damage. Causes serious eye damage. Symptoms may s, swelling, and blurred vision. Permanent eye damage including >1,250 mg/kg 1,300 mg/kg
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics Information on toxicological Acute toxicity Benzaldehyde Acute toxicity Benzaldehyde, 4-Hydroxy-3-	f exposure May cause irritation to the respir Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result. effects Not known. 100-52-7 LD50 Dermal-rabbit LD50 Oral-rat	e skin damage. Causes serious eye damage. Symptoms may s, swelling, and blurred vision. Permanent eye damage including >1,250 mg/kg
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics Information on toxicological Acute toxicity Benzaldehyde Acute toxicity Benzaldehyde, 4-Hydroxy-3- Methoxy	f exposure May cause irritation to the respir Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result. effects Not known. 100-52-7 LD50 Dermal-rabbit LD50 Oral-rat 121-33-5	e skin damage. Causes serious eye damage. Symptoms may s, swelling, and blurred vision. Permanent eye damage including >1,250 mg/kg 1,300 mg/kg
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics Information on toxicological Acute toxicity Benzaldehyde Acute toxicity Benzaldehyde, 4-Hydroxy-3- Methoxy Acute toxicity	f exposure May cause irritation to the respin Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result. effects Not known. 100-52-7 LD50 Dermal-rabbit LD50 Oral-rat 121-33-5 LD50 Oral-rat	e skin damage. Causes serious eye damage. Symptoms may s, swelling, and blurred vision. Permanent eye damage including >1,250 mg/kg 1,300 mg/kg
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics Information on toxicological Acute toxicity Benzaldehyde Acute toxicity Benzaldehyde, 4-Hydroxy-3- Methoxy Acute toxicity Ethanol, 2,2'-Iminobis Acute toxicity Silicic acid (H2SIO2), Sodium sa	f exposure May cause irritation to the respin Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result. effects Not known. 100-52-7 LD50 Dermal-rabbit LD50 Oral-rat 121-33-5 LD50 Oral-rat 111-42-2 LD50 Oral-rat	e skin damage. Causes serious eye damage. Symptoms may s, swelling, and blurred vision. Permanent eye damage including >1,250 mg/kg 1,300 mg/kg 1,580 mg/kg
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics Information on toxicological Acute toxicity Benzaldehyde Acute toxicity Benzaldehyde, 4-Hydroxy-3- Methoxy Acute toxicity Ethanol, 2,2'-Iminobis Acute toxicity Silicic acid (H2SIO2), Sodium so (1:2)	f exposure May cause irritation to the respin Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result. effects Not known. 100-52-7 LD50 Dermal-rabbit LD50 Oral-rat 121-33-5 LD50 Oral-rat 111-42-2 LD50 Oral-rat 6834-92-0	e skin damage. Causes serious eye damage. Symptoms may s, swelling, and blurred vision. Permanent eye damage including >1,250 mg/kg 1,300 mg/kg 1,580 mg/kg 710 mg/kg
products SECTION 11: TOXICOLOGICAL Information on likely routes of Inhalation Skin contact Eye contact Ingestion Symptoms related to the physical, chemical, and toxicological characteristics Information on toxicological Acute toxicity Benzaldehyde Acute toxicity Benzaldehyde, 4-Hydroxy-3- Methoxy Acute toxicity Ethanol, 2,2'-Iminobis Acute toxicity Silicic acid (H2SIO2), Sodium sa	f exposure May cause irritation to the respin Causes severe skin burns. Causes serious eye damage. Causes digestive tract burns. Burning pain and severe corrosiv include stinging, tearing, redness blindness could result. effects Not known. 100-52-7 LD50 Dermal-rabbit LD50 Oral-rat 121-33-5 LD50 Oral-rat 111-42-2 LD50 Oral-rat	e skin damage. Causes serious eye damage. Symptoms may s, swelling, and blurred vision. Permanent eye damage including >1,250 mg/kg 1,300 mg/kg 1,580 mg/kg 1,280 mg/kg 1,280 mg/kg

Serious eye damage/eye irritation	Causes serious eye damage.		
Respiratory sensitization	Due to partial or complete lack of data the classification is not possible.		
Skin sensitization	Due to partial or complete lack of data the classification is not possible.		
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.		
Carcinogenicty	Suspected of causing cancer.		
IARC	Ethanol, 2,2',2"-Nitrilotris- (CAS	L02-71-6) 3 No	t classifiable as to carcinogenicity to humans.
	Ethanol, 2,2'-Iminobis- (CAS 111	42-2) 2B P	ossibly carcinogenic to humans.
NTP	Not listed.		
OSHA	Not listed.		
Reproductive toxicity	Due to partial or complete lack o	f data the classifi	cation is not possible.
Specific target organ toxicity, single exposure	Due to partial or complete lack o	f data the classifi	cation is not possible.
Specific target organ toxicity, repeated exposure	Due to partial or complete lack o	f data the classifi	cation is not possible.
Aspiration hazard	Due to partial or complete lack o	f data the classifi	cation is not possible.
Chronic effects	Prolonged inhalation may be ha	mful. Prolonged e	exposure may cause chronic effects.
SECTION 12: ECOLOGICAL INFO			
Ecotoxicity	•	•	ardous. However, this does not exclude the
Benzaldehyde	100-52-7	ollis can have a ha	armful or damaging effect on the environment.
Toxicity to fish LC50	Bluegill (Lepomis macrochirus)	0.8 – 1.44 mg/l,	96 hours
Benzaldehyde, 4-Hydroxy-3- Methoxy-	121-33-5		
Toxicity to fish LC50	Fathead minnow (Pimephales promelas)	53 – 61.3 mg/l,	96 hours
Ethanol, 2,2',2"-Nitrilotris-	102-71-6		
Toxicity to crustacea EC50	Water flea (Ceriodaphnia dubia)	565.2 – 658.3 m	ng/l, 48 hours
Toxicity to fish LC50	Fathead minnow (Pimephales promelas	10,610 - 13,010) mg/l, 96 hours
Ethanol, 2,2'-Iminobis-	111-42-2		
Toxicity to crustacea EC50	Water flea (Ceriodaphnia dubia)	61.8 – 86.04 mg	
Toxicity to fish LC50	Fathead minnow (Pimephales promelas	100 mg/l, 96 ho	urs
Sodium Hydroxide (NA(OH))	1310-73-2		
Toxicity to crustacea EC50	Water flea (Ceriodaphnia dubia)	34.59 – 47.13 m	ng/l, 48 hours
Toxicity to fish LC50	Western mosquitofish (Gambusia affinis)	125 mg/l, 96 ho	urs
Persistence and degradability	No data is available on the degrad	ability of any ingr	edients in the mixture.
Bio-accumulative potential			
Partition coefficient n-octa	nol/water (log Kow)		
Benzaldehyde	1.48		
Benzaldehyde, 4-Hydroxy- 3-Methoxy-	1.37		
Ethanol, 2,2',2"-Nitrilotris-	-1		
Ethanol, 2,2'-Iminobis-	-1.43		
Mobility in soil	Not available.		
Other adverse effects			e depletion, photochemical ozone create cential) are expected from this component.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel] The waste code should be assigned in discussion between the user, the producer, and the waste disposal company.
Waste from residues/unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions.)
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: TRANSPORT INFORMATION

DOT INFORMATION FOR QUANTITIES GREATER THAN 5 LITERS PER CONTAINER.

UN number	UN3266	
UN proper shipping name	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (DISODIUM TRIOXOSILICATE)	
Transport hazard class(es)	Class	8
	Subsidiary risk	-
Packing group	III	
Special precautions for user	Read safety instruc	tions, SDS, and emergency procedures before handling.
ERG number	154	
Transportation information	on packaging may be	different from that listed.


DOT INFORMATION FOR QUANTITIES LESS THAN 5 LITERS PER JUG.

Shipping name	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (DISODIUM TRIOXOSILICATE), LIMITED QUANTITY
Special precautions for user	Read safety instructions, SDS, and emergency procedures before handling.
ERG number	154

Transportation information on packaging may be different from that listed.

IATA

UN number	UN3266
UN proper shipping name	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (DISODIUM TRIOXOSILICATE)
Transport hazard class(es)	Class 8
	Subsidiary risk -
Packing group	III
Environmental hazards	No.
ERG Code	154
Special precautions for user	Read safety instructions, SDS, and emergency procedures before handling.
IMDG	
UN number	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALCOHOLS, C9-11, ETHOXYLATED), MARINE POLLUTANT
Transport hazard class(es)	Class 9
	Subsidiary risk -
Packing group	III
Environmental hazards	Marine pollutant Yes.
EmS	F-A, S-F
Special precautions for user	Read safety instructions, SDS, and emergency procedures before handling.



General information	inibo Regulated Marine i oliutalit.			
SECTION 15: REGULATORY INFORMATION				
US federal regulations	This product is a "Hazardous (29 CFR 1910.1200.	This product is a "Hazardous Chemical" as defined by OSHA Hazard Communication Standard, 29 CFR 1910.1200.		
Toxic Substances Control	l Act (TSCA)			
TSCA Section 12(b) E	xport Notification (40 CFR 707, Suptp. D)	Not regulated		
CERCLA Hazardous S	Substance List (40 CFR 302.4)			
Ethanol, 2,2'-Im	inobis- (CAS 111-42-2)	Listed.		
Sodium Hydroxide (NA(OH)) (CAS 1310-73-2)		Listed.		

OSHA Specifically Regulated Substances (29 CFR 1910.1001- 1053)Not listed.Superfund Amendments and Reauthorization Act of 1986 (SARA)Not listed.SARA 302 Extremely hazardous substanceNot listed.SARA 311/312 Hazardous chemicalYesClassified hazard categoriesSkin corrosion or irritation Serious eye damage or eye irritation Carcinogenicity Not regulated.Other federal regulationsClean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Clean Air Act (CAA) Section 112® Accidental ReleaseNot regulated.	SARA 304 Emergency release notification	Not regulated.			
SARA 302 Extremely hazardous substanceNot listed.SARA 311/312 Hazardous chemicalYesClassified hazard categoriesSkin corrosion or irritation Serious eye damage or eye irritation Carcinogenicity Not regulated.Other federal regulationsClean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Clean Air Act (CAA) Section 112® Accidental ReleaseEthanol, 2,2'-Iminobis- (CAS 111-42-2)		Not listed.			
SARA 311/312 Hazardous chemicalYesClassified hazard categoriesSkin corrosion or irritation Serious eye damage or eye irritation Carcinogenicity Not regulated.SARA 313 (TRI reporting)Not regulated.Other federal regulationsClean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Clean Air Act (CAA) Section 112® Accidental ReleaseEthanol, 2,2'-Iminobis- (CAS 111-42-2) Not regulated.	Superfund Amendments and Reauthorization Act of 1986 (SARA)				
Classified hazard categories Skin corrosion or irritation Serious eye damage or eye irritation Carcinogenicity Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Clean Air Act (CAA) Section 112® Accidental Release Not regulated.	SARA 302 Extremely hazardous substance	Not listed.			
Serious eye damage or eye irritation Carcinogenicity Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Clean Air Act (CAA) Section 112® Accidental Release Not regulated.	SARA 311/312 Hazardous chemical	Yes			
Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants Ethanol, 2,2'-Iminobis- (CAS 111-42-2) (HAPs) List Clean Air Act (CAA) Section 112® Accidental Release Not regulated.		Serious eye damage or eye irritation Carcinogenicity			
(HAPs) List Clean Air Act (CAA) Section 112 [®] Accidental Release Not regulated.	Other federal regulations	C C			
		Ethanol, 2,2'-Iminobis- (CAS 111-42-2)			
Prevention (40 CFR 68.130)	Clean Air Act (CAA) Section 112 [®] Accidental Release Prevention (40 CFR 68.130)	Not regulated.			
Safe Drinking Water Act (SDWA) Not regulated.	Safe Drinking Water Act (SDWA)	Not regulated.			

State Regulations

California Proposition 65:



WARNING: This product can expose you to Ethanol, 2,2'-Iminobis-, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

California Proposition 65 – CRT: Listed date/Carcinogenic substance ETHANOL, 2,2'-IMINOBIS- (CAS 111-42-2) Listed: June 22, 2012 US California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3) subd. (a)) ETHANOL, 2,2'-IMINOBIS- (CAS 111-42-2) SODIUM HYDROXIDE (NA(OH)) (CAS 1310-73-2)

International Inventories

County or region	Inventory name	On inventory (yes/no)*
Canada	Domestics Substances List (DSL)	Yes
Canada	Non- Domestics Substances List (NDSL)	No
US & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
<i></i>	• · · · · · · · · · · ·	

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing county(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16: OTHER INFORMATION

Important Note: To be the best of our knowledge, the information contained herein is accurate. However there is no assumption of liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer/supplier, the manufacturer/supplier will not be responsible for loss, injury, or expense arising out of the products improper use. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

End of SDS